

DuraBlue L Series

Adhesive Melters

4, 10 and 16 liter melters

DuraBlue melters:

- Are easy to install
- Provide easy day-to-day operation
- Simplify routine maintenance

Nordson DuraBlue L Series melters feature fixed-speed AC motors with gerotor gear pumps for easy to operate, low-maintenance hot melt adhesive application. A non-stick coated, tube tank eliminates dead corners and minimizes adhesive char. Pump operation can be controlled by a handgun trigger or a foot switch.



Status-at-a-glance indicators graphically display the status of the tank, hose and gun



Large, accessible tank opening allows easier filling and cleaning



Easy-to-use controls eliminate complicated programming



Easy access panels make maintenance quick and simple

DuraBlue L Series Adhesive Melters

Specifications

Type of System	Tank with gerotor pump
Maximum Pump Rate ¹ (per hour)	22, 35 or 50 kg (48, 77 or 110 lb)
Number of Hoses/Guns	2
Filter Type ²	Saturn® basket-style filter
Maximum Working Hydraulic Pressure ³	75 bar (1100 psi)
Operating Temperature Range	40 to 230°C (100 to 450°F)
Ambient Temperature Range	0 to 50°C (32 to 122°F)
Temperature Control Stability	±0.5°C (1°F)
Electrical Service ⁴	120 VAC single phase 60 Hz 200 to 240 VAC single phase 50/60 Hz



Quick plug-in
hose/gun pairs

	DuraBlue 4 L	DuraBlue 10 L	DuraBlue 16 L
Holding Capacity 3.9 kg (8.6 lb)	4 L (244 in ³) 9.7 kg (21.4 lb)	10 L (610 in ³) 15.5 kg (34.1 lb)	16 L (976 in ³)
Throughput (per hour) ⁵	6.3 kg (13.9 lb)	12.5 kg (27.5 lb)	20 kg (44 lb)
Melt Rate (per hour) ⁵	4.7 kg (10.3 lb)	7.7 kg (17 lb)	11.2 kg (24.7 lb)
Maximum System Power Capacity			
@120 VAC	2400 watts	2400 watts	2400 watts
@240 VAC	3355 watts	3915 watts	4415 watts
Approx. Weight (empty)	42 kg (92 lbs)	76 kg (168 lbs)	80 kg (175 lbs)
Dimensions			
Width	334 mm (13.1 in.)	441 mm (17.4 in.)	441 mm (17.4 in.)
Height	478 mm (18.8 in.)	649 mm (25.5 in.)	649 mm (25.5 in.)
Depth	552 mm (21.7 in.)	620mm (24.4 in.)	620 mm (24.4 in.)

¹ Values shown for melter @ 60 Hz.

² Filter not available on all melters.

³ Maximum pressure varies by unit.

⁴ Permitted deviation from rated line voltage is ±10%.

⁵ At 240 volts; actual rates will vary depending on adhesive type, application parameters and input voltage.



240 VAC units are CE-compliant.
120 VAC units are C-UL listed.



For more information, speak with your Nordson representative or contact your Nordson regional office.

United States

Duluth, Georgia
(800) 683-2314 **Phone**
(866) 667-3329 **Fax**

Canada

Markham, Ontario
(800) 463-3200 **Phone**
(905) 475-8821 **Fax**

Europe

Erkrath, Germany
(49) 211-9205-0 **Phone**
(49) 211-254658 **Fax**

Japan

Tokyo, Japan
(81) 3-5762-2700 **Phone**
(81) 3-5762-2701 **Fax**

Asia/Australia/ Latin America

Amherst, Ohio
(440) 985-4797 **Phone**
(440) 985-1096 **Fax**

Find us on:

