

458 Skystep™ Red



- Ergonomically engineered, the SkyStep™ utilizes the power of air. The mat is designed to suction to the ground to prevent the mat from shifting while trapping air in its chambers. These air pockets combined with the resiliency of the rubber create an ultimate cushioning effect while keeping the mat lightweight.
- Made of high quality rubber for maximum durability and excellent standing comfort.
- This mat is grease resistant and offers simple solutions to almost any industrial or food service application. Its light weight facilitates handling when cleaning.
- Resilient rubber to provide fatigue relief, made of tough compound designed to yield a long service life.
- Aggressive slip resistant surfaces.
- The bubble surface provides a sure footing and optimal ergonomic effects in stationary standing positions.
- Moulded bevelled edges on all four sides to prevent tripping on the mat.
- Clean by sweeping or vacuuming.
- Resistant to most chemicals and extreme temperatures.
- Free of silicone therefore safe for vehicle painting facilities.

458 Skystep™ Red

PRODUCT SPECIFICATIONS			
Designation	Industrial matting		
Type	Anti-fatigue		
Description	Standalone Rubber Mats		
Material	75% nitrile rubber compound – Resistant to oils, grease and animal fats		
Process	Compression moulding		
Category	Better		
Recommended use	Medium duty – dry industrial environments		
Colours	Black		
Weight	10 kg/m ²		
Thickness	13 mm		
Standard sizes	60 cm x 90 cm 90 cm x 120 cm 90 cm x 150 cm		
Custom sizes	N/A		
Special remarks	N/A		
PRODUCT TESTING			
Tests	Norms	Results	
Foam battery	ASTM D3574		
Abrasion resistance	ASTM D3884-01		
	1000 Cycles	0.824	
	5000 Cycles		
Static coefficient of friction	ASTM C1028-96		
Elongation	ASTM D412	210%	
Breaking load	ASTM D412	4.80 Mpa	
Graves tear strength	ASTM D 1004	10.5 N/mm	
Hardness	ASTM D2240-02	67 Shore A	
Anti-slip	DIN 51130 and BG-RULE BGR181	R9	
MATERIAL ANALYSIS			
Compression Set @ 25%	ASTM D395		
Compression Deflection @ 25%	ASTM D575		
Compression Deflection @ 50%	ASTM D575		
Standard method for rubber deterioration	ASTM D1171		
FIRE TESTING			
	Critical radiant flux	ASTM E-648	
	Fire retardancy	DIN4102 EN 13501-1	
	Flammability test	ASTM D2859	5 min.
ESD	ANSI ESD S7.1 50% Humidity		
Sustainability	<ul style="list-style-type: none"> • Recyclable material • Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 		